

PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁷ : F02M 25/07, F16K 11/052, 11/14		A1	(11) International Publication Number: WO 00/28203
			(43) International Publication Date: 18 May 2000 (18.05.00)
(21) International Application Number: PCT/SE99/02029			(81) Designated States: AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, CZ (Utility model), DE, DE (Utility model), DK, DK (Utility model), DM, EE, ES, FI, FI (Utility model), GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SK (Utility model), SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).
(22) International Filing Date: 9 November 1999 (09.11.99)			
(30) Priority Data: 9803827-6 9 November 1998 (09.11.98) SE 9804240-1 7 December 1998 (07.12.98) SE			
(71) Applicant (for all designated States except US): STT HOLDING AB [SE/SE]; P.O. Box 7219, S-862 40 Njurunda (SE).			
(72) Inventors; and (75) Inventors/Applicants (for US only): ERIKSSON, Ingemar [SE/SE]; Garnvägen 15, S-862 91 Kvissleby (SE). BLOMQVIST, Micael [SE/SE]; Blåklintsvägen 3, S-862 34 Kvissleby (SE).			
(74) Agents: BJERKÉN, Håkan et al.; Bjerkéns Patentbyrå KB, P.O. Box 1274, S-801 37 Gävle (SE).			Published With international search report.
(54) Title: A METHOD AND DEVICE FOR AN EGR-SYSTEM AND A VALVE AS WELL AS A REGULATION METHOD AND DEVICE			
(57) Abstract			
<p>The invention is related to a method and a device for recirculation of a part of exhaust gases from an exhaust pipe (6, 9) of a diesel engine (1) to the inlet of the engine, the exhaust gases being diverted from the exhaust pipe (6, 9) and directed through a recirculation conduit (10) to a controllable valve device (12) arranged between the engine and the air intake (2) thereof for allowing supply of air/recirculated exhaust gases in a desired relation to the combustion chamber of the engine (1). The invention also relates to a particular valve having two controllable inlets, said valve being useful in the method or device according to the invention, and a regulation method and device for regulating the air/fuel relation of a diesel engine.</p>			

BEST AVAILABLE COPY

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece			TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	NZ	New Zealand		
CM	Cameroon			PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakhstan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LI	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		

5

A method and device for an EGR-system and a valve as well as a regulation method and device

- 10 The present invention is related to a method and a device for an EGR-system (Exhaust Gas Recirculation), particularly for use in heavy-duty diesel engines. The invention also relates to a valve which is particularly suited for the method and device according to the invention but the valve may also find use within other
15 fields. Finally, the invention is also related to a regulation method and device for a diesel engine.

In order to reduce the contents of hazardous exhaust gases, particularly nitrogen oxide (NOx), so called EGR-systems are
20 used since many years in many types of combustion engines. Such systems admit a part of the exhaust gases to be recirculated to the intake system of the engine, where it is mixed with the intake air and is conveyed further to the combustion chamber of the engine. The recirculated exhaust gases replace
25 a part of the intake air and have a reducing effect on the formation of NOx. A so called EGR-valve is then placed in connection with the exhaust system of the engine, the purpose of said valve being to regulate the amount of recirculated exhaust gases.

30

A method and a device according to the precharacterising parts of enclosed claims 1 and 6 are disclosed in DE A1 4 007 516. Although this prior art makes it possible to use an EGR-system in super charged diesel engines, where the pressure in the in-
35 take system downstream of the super charger is higher than the pressure in a recirculation conduit from an EGR-valve some

important disadvantages are inherent in this prior art. Thus, the valve device comprises separate dampers arranged in the EGR-recirculation channel and an air intake channel. Separate drive motors are provided for these dampers, a fact which makes the valve device complicated and this also applies for a control device therefor.

OBJECT OF THE INVENTION

A primary object of the present invention is to provide a method enabling a more reliable and simple regulation of the relation air/recirculated exhaust gases. As to the device according to the invention, the aim is to simplify the valve device and provide for a more reliable and simple control thereof.

A secondary object of the invention is to provide a valve suitable for mixing two fluids flowing through two inlet channels. Such a valve should be suitable for general purposes but is particularly useful in an EGR-system for diesel engines, including super charged diesel engines.

A tertiary object of the invention is to provide a regulation method and device providing for improved regulation possibilities with regard to a diesel engine provided with an EGR-system.

SUMMARY OF THE INVENTION

The primary object of the invention is achieved by the features defined in the characterising parts of claims 1 and 6. The design of the valve device as comprising two dampers, where at least one of the dampers always is open and where the other of the dampers is closable by means of a drive motor common to the dampers provides for a simple design and a reliable operation.

The secondary object of the invention is achieved by means of the valve as defined in the characterising part of claim 13.

5 The tertiary object of the invention is achieved by means of the regulation method and device as defined in the characterising parts of claims 16 and 18. Thus, this aspect of the invention is based on use of probes and sensors connected to a control device for the valve device so as to enable regulation not only of the relation air/recirculated exhaust gases but also regulation of
10 the air/fuel relation of the engine. This aspect of the invention provides for an improved overall regulation of the engine and a smaller amount of pollution.

15 Preferable developments of the basic aspects of the invention are defined in dependent claims.

The use of an EGR-system as contemplated by the invention on an engine provided with a catalyst and a particle filter according to the prior art results in a substantial reduction of the NOx
20 contents. This reduction may be up to 50% and makes it possible to upgrade existing diesel engines to present emission requirements and to upgrade modern diesel engines to future emission requirements.

25 BRIEF DESCRIPTION OF THE DRAWINGS

The invention will now be described by means of non-limiting embodiments illustrated in the drawings, where

30 Fig 1 illustrates a diagrammatical view of an EGR-system according to the invention;

Fig 2a illustrates a sectioned valve according to the invention in one end position;

35

- Fig 2b is a section view of the valve in Fig 2a as viewed in the direction of the arrow B-B;
- Fig 3a illustrates a sectioned valve according to the invention
5 in an intermediate position;
- Fig 3b illustrates a section view of the valve in Fig 3a as viewed in the direction of the arrow B-B;
- 10 Fig 4a illustrates a cut valve according to the invention in a second end position; and
- Fig 4b illustrates a section view of the valve in Fig 4a as viewed in the direction of the arrow B-B.

15

DETAILED DESCRIPTION OF PREFERRED EMBODIMENTS

Fig 1 is a diagrammatical view showing the parts, which are essential to the invention, of a combustion engine indicated with the reference character 1. The engine is in the selected embodiment example a turbo charged diesel engine but as already mentioned the engine may be a diesel engine without super charging or a diesel engine with a different type of super charging than a turbo charger. Air is taken to the engine 1 through an
20 air intake, an air filter 2, and is directed via an inlet air channel 3 to a turbo charger 4, where the air is super charged and then conveyed further through an intercooler 5, where the super charged air is cooled down before it is conveyed into the engine 1. The exhaust gases from the engine 1 are first directed
25 through the second side of the turbo charger 4, namely that side which is the driving one, and then through an exhaust pipe 6, a catalyst 7 and a particle trap 8 to finally be emitted to the open air via an end pipe 9.

35 From the end pipe 9, i.e. an extension of the exhaust pipe after the catalyst and particle trap, there is a branch, a recirculation

conduit 10, to recirculate from the exhaust gases a part thereof to the engine. The recirculation conduit 10 passes suitably through a cooler 11 to cool down the recirculated exhaust gases and it connects to the inlet air channel 3 via a valve device 12
5 controllable by means of an EGR control device 13. The valve device 12 may, with the assistance of the EGR control device 13, regulate the relation between the supplied amount of fresh air from the inlet air channel 3 and the supplied amount of recirculated exhaust gases from the recirculation conduit 10.

10 The EGR control device 13 regulating the valve device 12 is supplied with information about the actual operational state of the engine from a.o. a Lambda probe 14, a sensor 15 for the number of revolutions of the engine and a sensor 16 for engine
15 load and this control device is programmed to control the valve device 12 and, accordingly, the mixing relation fresh air/exhaust gases for the purpose of minimising the contents of hazardous substances leaving the end pipe 9 and being emitted into the open air. The programming of the EGR control device 13 occurs
20 in a previously known manner with regard to the relations between the different factors given hereinabove. As is well known, a Lambda probe provides an output signal varying with the oxygen contents of the exhaust gases. The engine load sensor 16 may for instance be a throttle position sensor and/or a
25 sensor sensing the amount of fuel injected to the engine. Also other sensors than those mentioned may be added to achieve a refined regulation.

The valve device 12 may comprise separate valves in the inlet
30 air channel 3 and in the recirculation conduit 10, said valves then being separately controllable by the EGR control device 13. Alternatively the valve device 12 may also comprise a unit, in which flows from the inlet air channel 3 and the recirculation conduit 10 may be selectively brought together, by means of
35 valves contained in the valve device, to a common output flow, which is conveyed further to the turbo charger for super charg-

ing and introduction into the engine via the intercooler 5. A particularly suitable valve device 12 in one unit is a particular part of the invention and will be described more closely hereunder.

5 The valve illustrated in Figs 2-4 is a type of mixing valve providing for mixing of two in-flowing fluids in such a manner that the in-flowing fluid in one of the two inlet channels may be regulated from 0 to maximum, and thereafter the in-flowing fluid in the second inlet channel from a maximum to 0.

10

In use of the valve according to the invention as illustrated in Figs 2-4 as a valve device 12 in the method or device according to the invention, the inlet air channel 3 is connected to the second inlet channel 18 of the valve, whereas the recirculation conduit 10 is connected to the first inlet channel 17 of the valve. Furthermore, there is in the valve an outlet channel 19, which in the present embodiment conveys the gases mixed in the valve to the turbo charger 4. In both inlet channels 17 and 18, there are dampers 20 and 21, which are pivotable between an open and a closed position by means of an adjustment motor 22, for instance a step motor, to open or close the inlet channels. The two dampers 20, 21 are placed on concentric axles 23, 24, which are rotatable by means of the adjustment motor 22 and an actuation pin 25 driven by the motor, said actuation pin being capable of pivoting actuation arms 26, 27 connected to the axles 23 and 24 respectively. The actuation arms 26, 27 are spring loaded by one or more springs 28, 29 to a normal position, illustrated in Fig 3, where both dampers 20, 21 are held in a position such that the inlet channels 17, 18 are open.

30

In the position illustrated in Fig 2a, b, which is a starting position, the adjustment motor 22 has, by means of its actuation pin 25 and by means of the actuation arm 26, rotated the damper 20 to a closed position, and thus, the first inlet channel 17 connected to the recirculation conduit 10 is closed and no exhaust gases may be recirculated to the turbo charger and the engine.

35

The second actuation arm 27 is maintained in its normal position by the spring 29, which means that the damper 21 in the second inlet channel 18 connected to the inlet air channel 3 is maintained in its normally opened position and allows free flow of inlet air through the valve via the outlet channel 19 to the turbo charger. The adjustment motor 22 is controlled by the EGR control device 13 to regulate the relation between fresh air via the inlet air channel 3 and recirculated exhaust gases via the recirculation conduit 10. In the position with the damper 21 open, the adjustment motor 22 may rotate, by means of its actuation pin 25 and by means of the actuation arm 26, the damper 20 from the entirely closed position shown in Fig 2a, b to the position which is shown in Fig 3a, b where also the damper 20 is in such a position that also the first inlet channel 17 is open. The adjustment motor may also adjust the damper 20 into any position between these two end positions.

The position illustrated in Fig 3a, b, which is the normal position for the adjustment motor 20, is such that the actuation pin 25 of the adjustment motor does not actuate any of the actuation arms 26, 27 but they are maintained by the springs 28, 29 in a normal position, where, accordingly, the dampers 20, 21 open both inlet channels 17, 18.

Fig 4a, b illustrates a position contrary to the one in Fig 2a, b. Thus, the adjustment motor 22 has by means of its actuation pin 25 and by means of the actuation arm 27 rotated the damper 21 to a closed position, which means that the connection of the inlet air channel 3 with the outlet channel 19 is entirely interrupted whereas on the contrary the first inlet channel 17 connected to the recirculation conduit 10 is entirely open and allows the recirculated exhaust gases to freely flow further through the outlet channel 19 and then to the turbo charger 4 and further on to the engine. However, by means of the adjustment motor 22, the damper 21 may be adjusted into any intermediate position between the end positions illustrated in

Figs 3 and 4 to allow a desired amount, controlled by the EGR control device 13, of fresh air to be mixed with the recirculated exhaust gases.

5 Thus, with the valve according to the invention it becomes possible to control, in a simple manner, a three-way valve having two inlets and having a normal position, where both inlets are open so that one or the other of the inlets may be controlled
10 steplessly whereas the remaining inlet is maintained open. The valve may of course be controlled in other manners than by means of the EGR control device 13 described above and it may be used in quite different connections than the one now described and where corresponding control properties are desirable.

15 In a regulation method according to the invention, a control device is used which is supplied with information from a lambda probe 14, a motor speed sensor 15 and an engine load sensor 16. The control device is connected to a valve device,
20 corresponding to the valve device 12 described hereinabove, for regulation of the in-flowing amounts of air and/or recirculated exhaust gases to the engine. This valve device is arranged between the air filter and the inlet channel of the engine and may, as also has been described for the valve device 12,
25 comprise separate valves in the inlet air channel and recirculation conduit, or a three-way valve of the kind also described hereinabove. The valve device is controllable in a corresponding manner as also described hereinabove, and the control device may therefore control, based on the input signals received, the
30 air/fuel relation of the engine by regulating the amount of in-flowing air and simultaneously regulating the relation between the supplied fresh air and recirculated exhaust gases. This aspect of the invention is applicable with or without supercharging.

35

With the regulation method and device according to the invention it is possible to further decrease the NO_x-contents in the exhaust gases exiting from the end pipe of a diesel engine.

CLAIMS:

- 5 1. A method for recirculating a part of exhaust gases from an exhaust pipe (6, 9) of a diesel engine (1) to an inlet of the engine, the exhaust gases being diverted from the exhaust pipe (6, 9) and directed through a recirculation conduit (10) to a controllable valve device (12) arranged between the engine and an air intake (2) thereof to enable supply of
10 air/recirculated exhaust gases in a desired relation to a combustion chamber of the engine, the valve device comprising dampers (20, 21) arranged in inlet channels (17, 18) for the recirculated exhaust gases and air respectively, characterized
15 in that at least one of the dampers (20, 21) always is maintained open and that the other damper (20, 21) is closed by means of a drive motor (22) common to the dampers.
2. A method according to claim 1, characterized in that the exhaust gases from the exhaust pipe (6, 9) are diverted after a
20 catalyst (7) and a particle filter (8).
3. A method according to claim 1 or 2, characterized in that the relation air/recirculated exhaust gases is regulated by means of a control device (13) controlling the valve device (12)
25 based on information (14, 15, 16) supplied as to the actual operational state of the engine (1).
4. A method according to any preceding claim, characterized in that the exhaust gases in the recirculation conduit (10) are
30 cooled in a cooler (11) arranged in the recirculation conduit (10).
5. A method according to any preceding claim, characterized in that in a super charged diesel engine the recirculated exhaust gases are supplied between the air intake (2) and a
35 super charger (4).

- 5 6. A device for recirculating a part of the exhaust gases from an exhaust pipe (6, 9) of a diesel engine (1) to an inlet of the engine, a recirculation conduit (10) being provided for diverting the exhaust gases from the exhaust pipe (6, 9) and directing them to a controllable valve device (12) arranged between the engine and an air intake (2) thereof for enabling supply of air/recirculated exhaust gases in a desired relation to a combustion chamber of the engine (1), the valve device comprising dampers (20, 21) arranged in inlet channels (17, 18) for the recirculated exhaust gases and air respectively, characterized in that the valve device is arranged to always maintain at least one of the dampers open and that a drive motor (22) common to the dampers is arranged to close the other of the dampers (20, 21).
- 10 7. A device according to claim 6, characterized in that the drive motor (22) of the valve device (12) is controlled by a control device (13) regulating, by means of the positions of the dampers (20, 21), the relation air/recirculated exhaust gases in the valve device (12) based on information (14, 15, 16) supplied as to the actual operational state of the engine.
- 15 8. A device according to any of claims 6-7, characterized in that the recirculation conduit (10) is connected to the exhaust pipe (6, 9) of the engine after the catalyst (7) and a particle filter (8).
- 20 9. A device according to any of claims 6-8, characterized by a cooler (11) arranged in the recirculation conduit (10) to cool the recirculated exhaust gases.
- 25 10. A device according to any of claims 6-9, characterized in that in a diesel engine having a super charger, the valve (12) is arranged between the air intake (2) and the super charger.
- 30 35

11. A device according to any of claims 6-10, characterized in that the drive motor is a step-motor (22) arranged to operate one of the dampers (20, 21) at a time and adjust the same into an arbitrary position.
- 5 12. A device according to any of claims 6-11, characterized in that both dampers (20, 21) in a normal position are spring loaded (28, 29) to an open position.
- 10 13. A valve for mixing two fluids flowing through two inlet channels (17, 18), characterized in that dampers (20, 21) are arranged in both inlet channels (17, 18), that at least one of the dampers always is open and that a common motor (22) is arranged to close the other of said dampers (20, 21).
- 15 14. A valve according to claim 13, characterized in that the motor is a step-motor (22) arranged to operate one of the dampers (20, 21) at a time and adjust the same into an arbitrary position.
- 20 15. A valve according to claim 13 or 14, characterized in that both dampers (20, 21) in a normal position are spring loaded (28, 29) to an open position.
- 25 16. A method for regulating a diesel engine, a part of the exhaust gases from the diesel engine being recirculated to the inlet thereof and a supply of fresh air and recirculated exhaust gases to the diesel engine being regulated by means of a valve device (12) controlled by a control device (13) to regulate the relation between the supplied fresh air and recirculated exhaust gases, characterized in that the control device (13) is supplied with information from a Lambda probe (14), an engine speed sensor (15) and an engine load sensor (16) so as to regulate the air/fuel relation of the diesel engine by means of said information and the valve device.
- 30
- 35

17. A regulating method according to claim 16, characterized in that a valve according to any of claims 13-15 is used as the valve device.

5 18. A regulating device for a diesel engine, comprising means (10) for recirculating a part of exhaust gases from the diesel engine to an inlet thereof and a valve device (12) controlled by a control device (13) for regulating supply of fresh air and recirculated exhaust gases to the diesel engine so as to
10 regulate the relation between supplied fresh air and recirculated exhaust gases, characterized in that a Lambda probe (14), an engine speed sensor (15) and an engine load sensor (16) are connected to the control device (13) to supply information thereto and that the control device (13) is
15 arranged to regulate the air/fuel relation of the diesel engine by means of said information and the valve device (12).

19. A device according to claim 18, characterized in that the valve device is a valve according to any of claims 13-15.

20

1 / 2




Fig. 1

2 / 2




Fig. 4a




Fig. 4b




Fig. 3a




Fig. 3b




Fig. 2a




Fig. 2b

INTERNATIONAL SEARCH REPORT

International application No.
PCT/SE 99/02029

A. CLASSIFICATION OF SUBJECT MATTER

IPC7: F02M 25/07, F16K 11/052, F16K 11/14

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC7: F02M, F16K

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

SE,DK,FI,NO classes as above

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	DE 4007516 A1 (KLÖCKNER-HUMBOLDT-DEUTZ AG), 12 Sept 1991 (12.09.91), column 2, line 22 - line 46, figure 1 --	16, 18
X	DE 19728353 C1 (DAIMLER-BENZ AKTIENGESELLSCHAFT), 24 Sept 1998 (24.09.98), column 3, line 40 - column 4, line 54, figures 1,2 --	16, 18
P,A	WO 9855759 A1 (SOUTHWEST RESEARCH INSTITUTE), 10 December 1998 (10.12.98), figure 2, abstract --	

☒ Further documents are listed in the continuation of Box C. ☒ See patent family annex.

* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"I" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance: the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance: the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search

4 February 2000

Date of mailing of the international search report

25-02-2000

Name and mailing address of the ISA/
Swedish Patent Office
Box 5055, S-102 42 STOCKHOLM
Facsimile No. +46 8 666 02 86

Authorized officer

Dan Ionesco / MR
Telephone No. +46 8 782 25 00

INTERNATIONAL SEARCH REPORT

International application No.

PCT/SE 99/02029

C (Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
-----------	--	-----------------------

A

US 5427141 A (K. OHTSUBO), 27 June 1995 (27.06.95),
figures 1-4, abstract

--

INTERNATIONAL SEARCH REPORT

International application No.
SE99/02029

Box I Observations where certain claims were found unsearchable (Continuation of item 1 of first sheet)

This international search report has not been established in respect of certain claims under Article 17(2)(a) for the following reasons:

1. ☐ Claims Nos.:
because they relate to subject matter not required to be searched by this Authority, namely:

2. ☐ Claims Nos.:
because they relate to parts of the international application that do not comply with the prescribed requirements to such an extent that no meaningful international search can be carried out, specifically:

Box II Observations where unity of invention is lacking (Continuation of item 2 of first sheet)

This International Searching Authority found multiple inventions in this international application, as follows:

Claims 1-15 relate to a method and a device for recirculating a part of exhaust gases of diesel engine and to a valve for mixing exhaust gases and fresh air.

Claims 16 and 18 relate to a method and a device for regulating a diesel engine depending on information from a lamda probe, an engine speed sensor and an engine load sensor.

.../...

1. ☐ As all required additional search fees were timely paid by the applicant, this international search report covers all searchable claims.
2. ☒ As all searchable claims could be searched without effort justifying an additional fee, this Authority did not invite payment of any additional fee.
3. ☐ As only some of the required additional search fees were timely paid by the applicant, this international search report covers only those claims for which fees were paid, specifically claims Nos.:

4. ☐ No required additional search fees were timely paid by the applicant. Consequently, this international search report is restricted to the invention first mentioned in the claims; it is covered by claims Nos.:

Remark on Protest

- ☐ The additional search fees were accompanied by the applicant's protest.
☐ No protest accompanied the payment of additional search fees.

INTERNATIONAL SEARCH REPORT

International application No.
PCT/SE99/02029

The inventions of claims 1-15 and of claims 16, 18 do not have common special technical features as required by PCT Rule 13.2.

INTERNATIONAL SEARCH REPORT

Information on patent family members

02/12/99

International application No.

PCT/SE 99/02029

Patent document cited in search report			Publication date	Patent family member(s)	Publication date
DE	4007516	A1	12/09/91	NONE	
DE	19728353	C1	24/09/98	EP 0889226 A US 5937651 A	07/01/99 17/08/99
WO	9855759	A1	10/12/98	AU 7726498 A US 5927075 A	21/12/98 27/07/99
US	5427141	A	27/06/95	NONE	

9804240-1 F02M 25/07

SVERIGE (A) ALLMÄNT TILLGÄNGLIG

(22) ANS DAT 1998-12-07 (21) ANS NR 9804240-1

(24) LÖPDAT 1998-12-07 ANSVK K1KC

(51) KLASS F02M 25/07

F16K 11/14

F16K 11/052

(41) OFF DAT 2000-05-10 (74) OMBUD Bjerkéns Patentbyrå KB

(71) SÖKANDE STT Holding AB
852 29 Sundsvall SE

(72) UPPFINNARE Ingemar Eriksson Kvissleby SE, Michael Blomqvist Kvissleby SE

(30) PRIORITETSUPPGIFTER
1998-11-09 SE 9803827-6

(54) BENÄMNING Förfarande och anordning för ett EGR-system, samt ventil

(57) SAMMANDRAG

Uppfinningen avser ett förfarande och en anordning för återföring av en del av avgaserna från avgasröret (6, 9) hos en dieselmotor (1) till motorns inlopp, varvid avgaserna avleds från avgasröret (6, 9) och leds genom en återföringsledning (10) till en styrbar ventilanordning (12) anordnad mellan motorn och dess luftintag (2) för att medge tillförsel av luft/återcirkulerade avgaser i önskat förhållande till motorns (1) förbränningsrum. Uppfinningen avser även en speciell ventil med två styrbara inlopp, som kan användas vid förfarandet eller anordningen enligt uppfinningen.




Fig. 1

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ BLACK BORDERS
- ☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☐ FADED TEXT OR DRAWING
- ☒ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☐ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☒ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.